

S&R SIMULATED 20MIN-FIRE RATING
 SIMSR_20N_INT | SIMSR_20B_INT
 Architectural Series



	SERIES	ARCHITECTURAL
FIRE RATING	Label	Warnock Hershey - Intertek / NFPA Compliance
	Pressure	Neutral, Cat B
DIMENSIONS	Thickness	1-3/4"
	Maximum Sizes	For Max Sizes, please review WKS Door Systems Fire Rating Chart
CONSTRUCTION	Ply	5 PLY Bonded/ No Bonded
	Core	Intumescent Core
	Vertical Edges	SCL Stile, Painted Edges
		Standard Bevel 1/8" in 2"
	Horizontal Edges	SCL Top & Bottom Rails (Rails Reinforcement, Sealed Top & Bottom Rais upon request)
	Crossband	One Piece High Density Fiberboard (HDF)
	Factory Finish	WDMA TR-8 / AWS SYSTEMS 9, UV Cured Acrylated - Polyurethane
	Paint Grade	One Piece High Density Fiberboard (HDF)
	Factory Finish	Primed Factory Finish or Solid Colors
Adhesive/ Weight	Type 2 / 32.3 kg/mt2 - 6.61 lb/ft2	
ELEVATIONS	Vision Lites	N/A
	Reveals	Allowed with restrictions, consult with your ISR
	Louvers	N/A
STC	Sound Rating	30 STC with installed seals and gaskets tested Automatic Bottom Seal and Threshold is recommended by WKS for a high performance
QUALITY STANDARDS	Environmental	FSC Credit MR7 available upon request
		CARB Phase 2 / TSCA VI Compliant
	Performance	Heavy, Extra Heavy Duty per WDMA I.S.1A Architectural Wood Flush Doors
	Warranty	Interior Use Only (no exterior warranty). Lifetime; life of original installation
Machining	Hardware preps shall be factory machined from manufacturer's templates and shop drawings	

Fire Rated Doors are manufactured per the standards listed on this page. Specifications are subject to the label listing and may change without notice. To ensure please contact your WKS Door Systems representative.

