

S&R SIMULATED-NON RATED
SIMSR_NR_TUB
Architectural Series



	SERIES	ARCHITECTURAL
DIMENSIONS	Thickness	1-3/4"
	Maximum Sizes	For Max Sizes, please consult with your ISR
CONSTRUCTION	Ply	5 PLY Bonded/ No Bonded
	Core	Extruded Tubular per Label Listing
	Vertical Edges	SCL Stile, Painted Edges Standard Bevel 1/8" in 2"
	Horizontal Edges	SCL Top & Bottom Rails (Rails Reinforcement, Sealed Top & Bottom Rais upon request)
	Crossband	One Piece High Density Fiberboard (HDF)
	Factory Finish	WDMA TR-8 / AWS SYSTEMS 9, UV Cured Acrylated - Polyurethane
	Paint Grade	One Piece High Density Fiberboard (HDF)
	Factory Finish	Primed Factory Finish or Solid Colors
	Adhesive/ Weight	Type 2 / 32.3 kg/mt2 - 6.61 lb/ft2
ELEVATIONS	Vision Lites	N/A
	Reveals	Allowed with restrictions, consult with your ISR
	Louvers	N/A
STC	Sound Rating	30 STC with installed seals and gaskets tested Automatic Bottom Seal and Threshold is recommended by WKS for a high performance
QUALITY STANDARDS	Environmental	FSC Credit MR7 available upon request CARB Phase 2 / TSCA VI Compliant
	Performance	Heavy, Extra Heavy Duty per WDMA I.S.1A Architectural Wood Flush Doors
	Warranty	Interior Use Only (no exterior warranty). Lifetime; life of original installation
	Machining	Hardware preps shall be factory machined from manufacturer's templates and shop drawings

