

**SOLUTEX NON RATED**  
**WDNR\_SLTX**  
*Architectural Series*



	SERIES	ARCHITECTURAL
DIMENSIONS	Thickness	1-3/4"
	Maximum Sizes	For Max Sizes, please consult with your ISR
CONSTRUCTION	Ply	3 PLY Bonded / No Bonded
	Core	Particleboard Core, ANSI A208.1, Grade LD-1
	Vertical Edges	Moisture Resistant Stiles with Matching Edgeband Over, Sealed Vertical Stiles, Standard Bevel 1/8" in 2"
	Horizontal Edges	Moisture Resistant Top & Bottom Rails with Matching Edgeband Over, Sealed Top & Bottom Rails (Rails Reinforcement upon request)
	Laminated Surface	Compact Laminate Phenolic Solid Plastic 1/8" thickness, Solid Colors and Patterns
	Adhesive/ Weight	Composite Urethane / PUR / 32.3 kg/mt2 - 6.61 lb/ft2
ELEVATIONS	Vision Lites	N/A
	Reveals	N/A
	Louvers	N/A
STC	Sound Rating	32 STC with installed seals and gaskets tested
		Surface Bottom Seal is recommended by WKS for a high performance
QUALITY STANDARDS	Environmental	FSC Credit MR7 available upon request
		CARB Phase 2 / TSCA VI Compliant
	Performance	Heavy, Extra Heavy Duty per WDMA I.S.1A Architectural Wood Flush Doors
	Warranty	For Semi-Exterior Use (Not Outdoors**) One (1) Year Limited Warranty
	Machining	Hardware preps shall be factory machined from manufacturer's templates and shop drawings

